

Appln. No. 09/717,767

Attorney Docket No. 5709-159

**II. Listing of Claims**

1. (Currently Amended): A two piece weatherstrip for a motor vehicle comprising, in combination,

a cover including a first flange portion, a second flange portion and a centrally disposed web, said first and second flange portions defining an outer surface,

a body including a first slot and an adjacent first face and an adjacent, oppositely disposed second slot and an adjacent second face, ~~one of said slots said first slot~~ adapted to receive said web and said second slot adapted to receive a flange of said motor vehicle, at least one wiper flange extending from said ~~first~~ second face, a flexible flange ~~adapted to engage a portion of~~ extending from said first face and having a terminal portion for engaging said motor vehicle and including a curved recess between said ~~flexible flange~~ terminal portion and said second ~~first~~ face for receiving a complementary portion of one of said flange portions of said cover.

2. (Currently Amended): The two piece weatherstrip of Claim 1 wherein said one of said flange portions defines a radiused rounded end and said recess of said body is complementarily radiused rounded.

3. (Original): The two piece weatherstrip of Claim 1 further including flocking disposed on said at least one wiper flange.

4. (Original): The two piece weatherstrip of Claim 1 including at least two wiper flanges.

5. (Cancelled):

6. (Original): The two piece weatherstrip of Claim 1 wherein said body further includes an S-shaped metal insert.

7. (Original): The two piece weatherstrip of Claim 1 wherein said body includes pluralities of obliquely disposed webs in said slots.

BRINKS  
HOFFER  
GILSON  
ALONE

Appln. No. 09/717,767

Attorney Docket No. 5709-159

8. (Original): The two piece weatherstrip of Claim 1 wherein said centrally disposed web of said cover includes an asymmetrical notch.

9. (Currently Amended): A two piece weatherstrip for a vehicle comprising, in combination,

a cover including first and second flanges defining an outer surface and a centrally disposed web extending from said cover on a side opposite said outer surface, and

a body including a pair of adjacent, oppositely disposed slots, one of said slots adapted to receive said web of said cover and another of said slots adapted to receive an edge of said vehicle, a third flange extending from said body adjacent said one of said slots and ~~adapted to engage~~ having a flexible terminal portion for engaging a portion of said vehicle, a recess adjacent formed in said third flange ~~adapted to receive for receiving a complementary~~ portion of one of said flanges of said cover and a wiper extending from said body adjacent said another of said slots and ~~adapted to engage for engaging~~ a window.

10. (Original): The two piece weatherstrip of Claim 9 further including low-friction material on said wiper.

11. (Original): The two piece weatherstrip of Claim 9 wherein said body further includes an S-shaped metal insert.

12. (Currently Amended): The two piece weatherstrip of Claim 9 wherein one of said flanges defines a ~~radiused~~ rounded end and said recess of said body is complementarily ~~radiused~~ rounded to receive said radiused end.

13. (Original): The two piece weatherstrip of Claim 9 wherein said body includes pluralities of obliquely disposed webs in said slots.

14. (Original): The two piece weatherstrip of Claim 9 wherein said centrally disposed web of said cover includes an asymmetrical notch.

BRINKS  
HOFFER  
GILSON  
ALLIANCE

Appln. No. 09/717,767

Attorney Docket No. 6709-159

15. (Currently Amended): A two piece outer belt weatherstrip for a vehicle door comprising, in combination,

a cover including first and second flanges defining an outer surface and a centrally disposed web, one of said first and said second flanges defining a curved end, and

a body including an S-shaped metal channel and defining a first slot and a second adjacent, oppositely disposed slot, one of said slots adapted to receive said centrally disposed web of said cover and another of said slots adapted to receive a flange of said vehicle, a wiper flange extending from said body adjacent said another of said slots, a vehicle engaging edge and flange extending from said body adjacent said one of said slots and having a complementary recess between said vehicle engaging edge and said one of said slots for receiving an said curved end portion of said one of said first and second flanges.

16. (Original): The two piece outer belt weatherstrip of Claim 15 further including flocking disposed on said at least one wiper flange.

17. (Original): The two piece outer belt weatherstrip of Claim 15 wherein said body includes pluralities of obliquely disposed webs in said slots.

18. (Previously Presented): The two piece outer belt weatherstrip of Claim 15 wherein said centrally disposed web of said cover includes an asymmetrical notch.

19. (Original): The two piece outer belt weatherstrip of Claim 15 including at least two wiper flanges.

BRINKS  
HOFFER  
GILSON  
ALIONE